| FCX4000 SERIES BLADES | | | | | |
|-----------------------|------------|--------------------------|--|--|--|
| | CB09UB | Angle 45° Diameter 0.9mm | Standard blade for vinyl cutting & self-adhesive marking film (PVC film) up to 0.25 mm thick. Maximum cutting distance is approx. 13,123 ft. | | |
| - | CB09UB-K60 | Angle 30° Diameter 0.9mm | Supersteel Blade for cutting the window tint film or thin film, up to 0.25 mm thick. | | |
| | CB15U | Angle 45° Diameter 1.5mm | Supersteel blade for cutting rigid or thicker media, 0.25 mm to 0.5 mm thick. (laminates, smart device, device screen protection media) | | |
| | CB15U-K30 | Angle 60° Diameter 1.5mm | Supersteel Blade for cutting rigid media, 0.25 mm to 0.5 mm thick. And also small detailed characters on marking film (up to 0.25mm). Recommended blade for sandblast rubber resist media cutting and Avery Series of Reflective sheeting. | | |
| | CB15UA | Angle 45° Diameter 1.5mm | Supersteel Blade for cutting high-intensity reflective film or harder film. | | |
| | CB15UA-K30 | Angle 60° Diameter 1.5mm | Supersteel Blade for cutting rigid media, 0.25 mm to 0.5 mm thick. And also small detailed characters on marking film (up to 0.25mm). Recommended blade for sandblast rubber resist media cutting and Avery Series of Reflective sheeting. | | |

NOTE: UA Blades are recommended for rigid medias due to their modified blade tip

| FCX4000 SERIES | | GRAP BLADE HOLDERS |
|----------------|--|--|
| | PHP31 FIBERSTEADTLER | FIBERSTEADTLER Lumocolor Fiber Tip Pen Holder. |
| | PHP33-CB09N-HS SPRING BUILT-IN TYPE | Compatible with Blades: CB09UA • CB09UA-K60 • CB09UB • CB09UB-K60 0.9mm, blue top, black ABS tip. Not recommended for CB09UA blades with springs. |
| | PHP33-CB15N-HS SPRING BUILT-IN TYPE | Compatible with Blades: CB15U • CB15U-K30* • CB15UA • CB15U-K20-2SP • CB15UA-K30 • CB15UB 1.5mm**, red top, black ABS tip. |
| | PHP34-BALL | Ballpoint pen holder for black, oil based pen (KB700-BK) |
| | PHP35-CB09-HS SPRING BUILT-IN TYPE | Compatible with Blades: CB09UA • CB09UA-K60 • CB09UB • CB09UB-K60 0.9mm, blue top, black brass tip. ATTENTION: If you are using CB09UA Blade (with spring); Insert only the CB09UA blade without the spring. This blade-holder, plunger design already includes an internal spring. These brass tip blade-holders, plungers are more rigid and lend to more accurate cutting. |
| | PHP35-CB15-HS SPRING BUILT-IN TYPE | Compatible with Blades: CB15U • CB15U-K30* • CB15UA • CB15U-K20-2SP • CB15UA-K30 • CB15UB 1.5mm***, red top, black brass tip. These brass tip blade-holders/plungers are more rigid & lend to more accurate cutting. NOTE: REMOVE CB15 SP Blade spring before installing into this Blade-holder. DO NOT install any blade spring to more accurate cuts. |
| Que and | PHP71-SHARPIE | Sharpie Pen holder with a metal sleeve that can be used with our FC & CE Cutters |

Recommended Setting On Control Panel for Small Detailed Figure and Character Cutting: CB15U-K30 Offset +2, Force 10-14, Speed 30 or less, Acceleration 3

CE6000-40, 60 and 120 Plus only. *CB15U-K30 can not be selected as the tool type. Please select (OTHER) instead.

| FCX4000 SERIES | | GREASING TOOLS |
|----------------|-----------|--|
| | CP-001 | Stick type tool for creasing heavy paper |
| | PM-CT-002 | Pen type creasing tool for curves on heavy paper |
| | CPGA-011 | Creasing tool with 0.02" fine tip for creasing paper |
| | CPGA-012 | Creasing tool with 0.05" tip for creasing cardboad |